

ISO/IEC 15961-2 DATA CONSTRUCTS REGISTER

Committee Approved: 2016-05-25



Data Constructs

There are four data constructs that are registered under the registration rules of ISO/IEC 15961-2:

- The AFI, used as a tag selection mechanism across the air interface to minimise the extent of communication transaction time with tags that do not carry the relevant AFI code.
- The data format, basically to enable a truncated or short form encoding of Object Identifiers (OIDs).
- The Object Identifier of the unique item identifier (UII). The UII is unique within the domain of the application and as defined by the scope of an application.
- The Object Identifier for other data that is possible to encode on the RFID tag. This is registered as a root-OID (as illustrated in the registered values).

Throughout the register hexadecimal values are shown using the format 0xHH, while decimal values are shown without any subscript.

There is a machine-readable table that shows the relationship of some of the data constructs, particularly the AFI relationship with the Object Identifier for the UII. When the data construct registers a Monomorphic-UII, this machine-readable table also specifies the encoding scheme used.

In addition, there are registrations of particular machine-readable tables used for some of the encoding schemes. These cover the following:

- Packed Objects
- Tag Data Profiles
- Mapping Tables (used to convert alphabetical or alpha-numeric codes to a numeric Relative-OID)

AFI Assignments

This table is shown separately, because the Registration Authority expects that some AFIs can be used for different applications in a non-conflicting manner. The AFI codes are shown as hexadecimal values.

| AFI (HEX) | Assigned Organisation or Function | Comments |
|--------------|--|---|
| 0x90 | Odette for Vehicle Identification Number Monomorphic-UII using 6-bit compaction in ISO/IEC 18000-63 tags | The VIN code is defined in ISO 3779 and applicable globally |
| 0x91 | IATA – for asset control, initially for ULD containers for cargo and passenger use | Compliant with IATA RP1640 standard |
| 0x92 | ISO/IEC JTC1 SC31 Secretariat | For use with ISO/IEC 20248 |
| 0x93 to 0x9F | RESERVED | |
| 0xA0 | IPC – for postal items Monomorphic-UII using URN Code 40 compaction in ISO/IEC 18000-63 tags | |
| 0xA1 | Monomorphic-UII using 6-bit compaction for ISO 17367 product tagging | |
| 0xA2 | Monomorphic-UII using 6-bit compaction for ISO 17365 transport unit | |
| 0xA3 | Monomorphic-UII using 6-bit compaction for ISO 17364 returnable transport unit | |
| 0xA4 | Monomorphic-UII using 6-bit compaction for ISO 17367 product tagging, but for hazardous materials | |
| 0xA5 | Monomorphic-UII using 6-bit compaction for ISO 17366 product packaging | |
| 0xA6 | Monomorphic-UII using 6-bit compaction for ISO 17366 product packaging, but for hazardous materials | |
| 0xA7 | Monomorphic-UII using 6-bit compaction for ISO 17365 transport unit, but containing hazardous materials | |
| 0xA8 | Monomorphic-UII using 6-bit compaction for ISO 17364 returnable transport unit, but containing hazardous materials | |
| 0xA9 | EXPLICITLY RESERVED FOR ISO 17363 | |
| 0xAA | EXPLICITLY RESERVED FOR ISO 17363 | |

| AFI (HEX) | Assigned Organisation or Function | Comments |
|--------------|---|---|
| 0xAB | UII scheme and encoding format for Mobile AIDC services as defined in ISO/IEC 29174 | |
| 0xAC to 0xAF | RESERVED | |
| 0xB0 | 6C Toll Operators Coalition Monomorphic-UII using 8-bit (Octet) compaction in ISO/IEC 18000-63 tags | |
| 0xBA | RESERVED | |
| 0xBB | ISBT – for blood, tissue, organ and cellular therapy products | Compliant with ISBT 128 & ISBT RFID Guidelines Because the encoding is not compliant with ISO/IEC 15962 Access Methods, the DSFID for this application is 0x3E |
| 0xBC to 0xBF | RESERVED | |
| 0xC0 | RESERVED for future assignment to an application that does not use ISO/IEC 18000-3M1 tags. | See Note 1 |
| 0xC1 | IATA – for baggage handling | Compliant with IATA RP1740C standard |
| 0xC2 | EDItEUR – for library items when on loan Using ISO/IEC 18000-3M1 tags | Compliant with ISO 28560 Parts 2 and 3 |
| 0xC2 | EDItEUR – for library items when on loan Monomorphic-UII using URN Code 40 compaction in ISO/IEC 18000-63 tags | Compliant with ISO TS 28560 Part 4 |
| 0xC3 to 0xCF | RESERVED | |

Additional Notes:

1. AFIs 0x90, 0xA0, 0xB0, and 0xC0 shall not be assigned to an application that may use ISO/IEC 18000-3 Mode 1 tags. There are claims from some vendors that the trailing "0" acts as a "wild card", but there are no statements supporting this claim in the standard.

Data Format Table

This table is shown separately, because the Registration Authority expects that some Data Formats can be used for different applications in a non-conflicting manner. The Data Formats are shown as decimal values.

| Data Format (Decimal) | Assigned Organisation or Function | Root-OID | Comments |
|-----------------------|-----------------------------------|--|---|
| 0 | Not-Formatted | Not applicable | This value is the default for an RFID tag yet to be formatted, so the system may assume that the tag has no encoded data The DSFID combining the Data Format with the Access Method) shall be 0x00. |
| 1 | Full-Featured | Not applicable | This is used where each OID has to be encoded in full, i.e. without truncating the Root-OID. This is relevant where the RFID tag is likely to contain a mixture of OIDs from different domains, or one from a minor domain. |
| 2 | Root-OID-Encoded | Encoded on the tag | This is useful for small domains requiring to encode a set of data. This data format requires the Root-OID to be encoded, but then truncates all OIDs so that only the Relative-OID needs to be encoded. |
| 3 | ISO/IEC 15434 | 1 0 15434 | This standard supports a number of message structures originally intended for two-dimensional bar codes. An efficient encoding scheme is defined in ISO/IEC 15962:2013 in Annex T and Annex U. |
| 4 | ISO/IEC 6523 | RESERVED for ICD 1 0 6523 (as assigned in ISO/IEC 15961:2004) | This standard deals with the registration of domains to the level of the International Code Designator (ICD). This data format allows existing organisation structures to be supported with the minimum of change. A list of ICDs up to number 0183 is at: http://www.oid-isnfo.com/get/1.3 and at http://www.cyber-identity.com/download/ICD-list.pdf . Registration under ISO/IEC 15961-2 should be for a particular ICD, and not all ICDs. |
| 5 | ISO/IEC 15459 | 1 0 15459 | ISO/IEC 15459 provides a mechanism to support unique identification codes across multiple industry and commercial sectors. The various parts of this standard provide the basis for track and trace codes for all levels in supply chains. |
| 6 | ISO 28560-2 and ISO TS 28560-4 | 1 0 15961 6 | These standards address the encoding of data on RFID tags in the library community and defines all the Relative-OID values |
| 7 | ISO/IEC 29174 | 2 27 | This root-OID applies only to the Relative-OID {1} for the unique Mobile Item Identifier (MII) |

| Data Format (Decimal) | Assigned Organisation or Function | Root-OID | Comments |
|-----------------------|--|--------------|--|
| 8 | ISO/IEC 15961-Combined | 1 0 15961 | This allows any combinations of OID that have the common root-OID {1 0 15961} to be encoded. The relative-OID then becomes the next arc (which can differ for different objects) followed by another arc identifying the particular data element. The structure was developed so that two, or more, related organisation could share encoding - by agreement – without one having all the encoding efficiencies. Joint registration by the relevant organisation should be a requirement for data constructs to be assigned. |
| 9 | GS1-AI | 1 0 15961 9 | This data format enables GS1 Application Identifiers to be used as the Relative-OID in an Object Identifier structure |
| 10 | ANS-DI-Algorithm | 1 0 15961 10 | This data format enables ANS MH10 Data Identifiers to be used as the Relative-OID in an Object Identifier structure. The alphanumeric DI is converted to a Relative-OID using an algorithm defined ISO/IEC 15961:2004 The preferred option for new applications is to use Data Format 13, which provides for more efficient encoding |
| 11 | IATA-Asset | 1 0 15961 11 | The data format is assigned to IATA for various low volume asset control applications, each of which will be registered. The Relative-OID values are assigned in various IATA standards, specifically: IATA RP1640 standard for ULD containers |
| 12 | IATA-Baggage | 1 0 15961 12 | The Relative-OID values are defined in the IATA RP1740C standard |
| 13 | ANSI-DI-Mapping Table | 1 0 15961 13 | This data format enables ANS MH10 Data Identifiers to be used as the Relative-OID in an Object Identifier structure in a more efficient encoding manner than data format 10. The current mapping table is available at: http://www.mhi.org/standards/di The mapping table is accessible from this link on the page: Assigned Relative OIDs 20140617.xls |
| 14 | IPC-Postal | 1 0 15961 14 | |
| 15 | 6C Toll Operators Coalition | 1 0 15961 15 | The Data Format only applies to the UII encoded in MB 01 of the 18000-63 tag. Data Format 30 is for MB 11, indicating that the encoding is based on a bit structure defined by the 6C Toll Operators Coalition |
| 16 | Odette for Vehicle Identification Number | 1 0 15961 16 | The Data Format only applies to the UII encoded in MB 01 of the 18000-63 tag. Data Formats 3 or 13 are used for MB 11, depending on the choice of the vehicle manufacturer |

| Data Format (Decimal) | Assigned Organisation or Function | Root-OID | Comments |
|-----------------------|---|--------------------------|---|
| 17 | ISO/IEC 20248 | 1 0 20248 | Digital Signatures for RFID |
| 18 to 28 | RESERVED | | |
| 29 | Closed system data fully encoded to ISO/IEC 15962 rules | The Root-OID is implied. | This Data Format enables closed system or prototype data to be encoded in a manner compliant with the ISO/IEC 15962 encoding rules (i.e. by declaring the relevant Access Method). As those implementing the application know the interpretation of the Relative-OID values, the Root-OID is implied and does not require to exist or to be registered. |
| 30 | Closed system data not encoded to ISO/IEC 15962 rules | Not applicable | The complete DSFID shall be one of the following: 0x1E, 0x3E, 0x5E, 0x7E, 0x9E, 0xBE, 0xDE, 0xFE. These values indicate that the encoded bytes are passed through unchanged in ISO/IEC 15962 and ISO/IEC 24791 implementations |
| 31 | Extended Data Format | Not applicable | Various extension mechanisms are included in ISO/IEC 15962 Rev1 for the DSFID; one enables an additional 256 Data Formats to be assigned. If the First DSFID has the value 0x0F, then the Data Format that is encoded is one that is defined in the following rows on this table. |
| 32 to 287 | RESERVED | | |

Data Constructs Register

The Data Constructs Register shows the combination of assignments of AFIs, Data Formats, together with the registration of Object Identifiers to organisations and to functions. In addition, the table indicates whether the Unique Item Identifier (UII) is encoded in a separate memory from other item-attendant data. The table clearly shows that it is the combination of AFI and Data Format(s) that provide the unique interpretation of data encoded on the RFID tag. This table is presented in AFI byte sequence.

Where a tag supports different memory areas for the UII and other Item-related data (e.g. ISO/IEC 18000-3 Mode 3, ISO/IEC 18000-63 [Type C] and ISO/IEC 18000-64 [Type D]) the **Data Format for additional data** column is encoded in the item-related memory area. This Data Format, and its associated Root-OID, may differ from that in the UII memory.

| Organisation or Standard | AFI (HEX) | UII Encoded Data Format (Decimal) | Monomorphic-UII Compaction | Monomorphic-UII MH10 Data Identifier | Object Identifier for Unique Item Identifier (UII) | Data Format for additional data (Decimal) |
|--|-----------|-----------------------------------|-----------------------------------|--------------------------------------|--|---|
| Odette for Vehicle Identification Number (using 18000-63 tags, with separate UII memory) | 0x90 | 16 | 6-bit | Not applicable | 1 0 15961 16 | 3 or 13 |
| IATA RP1640 ULD containers (using 18000-63 tags, with separate UII memory) See Note A | 0x91 | 11 | Not applicable | | 1 0 15961 11 5 | 11 |
| ISO IEC JTC1 SC31 Secretariat for ISO/IEC 20248 digital signatures for RFID, when using partitioned memory tags, e.g. ISO/IEC 18000-63 | 0x92 | Not applicable | Application-defined 8-bit (octet) | Not applicable | 1 0 20248 1 | 17 |
| ISO IEC JTC1 SC31 Secretariat for ISO/IEC 20248 digital signatures for RFID, when using single memory tags, e.g. ISO/IEC 18000-3M1 | 0x92 | 17 | Not applicable | Not applicable | 1 0 20248 1 | 17 |
| IPC: postal items (for 18000-63 tags, with separate UII memory) | 0xA0 | Not applicable | URN Code 40 | Not applicable | 1 0 15961 14 X See Note B | 14 |
| ISO 17367: supply chain applications of RFID – product tagging [separate UII memory, with Data Identifiers in separate memory] | 0xA1 | Not applicable | 6-bit | 25S | 1 0 15961 13 1 | 3 or 13 |
| | | | | 25T | 1 0 15961 13 3 | |
| | | | | I | 1 0 15961 13 96 | |
| ISO 17365: supply chain applications of RFID – transport unit [separate UII memory, with Data Identifiers in separate memory] | 0xA2 | Not applicable | 6-bit | J | 1 0 15961 13 4 | 3 or 13 |
| | | | | 1J | 1 0 15961 13 36 | |
| | | | | 2J | 1 0 15961 13 156 | |
| | | | | 3J | 1 0 15961 13 157 | |
| | | | | 4J | 1 0 15961 13 159 | |
| | | | | 5J | 1 0 15961 13 37 | |
| | | | | 6J | 1 0 15961 13 38 | |
| ISO 17364: supply chain applications of RFID – returnable transport item [separate UII memory, with Data Identifiers in separate memory] | 0xA3 | Not applicable | 6-bit | 1B | 1 0 15961 13 112 | 3 or 13 |
| | | | | 25B | 1 0 15961 13 2 | |
| ISO 17367: supply chain applications of RFID – product tagging, containing hazardous materials [separate UII memory, with Data Identifiers in separate memory] | 0xA4 | Not applicable | 6-bit | 25S | 1 0 15961 13 1 | 3 or 13 |
| | | | | 25T | 1 0 15961 13 3 | |
| | | | | I | 1 0 15961 13 96 | |

| Organisation or Standard | AFI (HEX) | UII Encoded Data Format (Decimal) | Monomorphic-UII Compaction | Monomorphic-UII MH10 Data Identifier | Object Identifier for Unique Item Identifier (UII) | Data Format for additional data (Decimal) |
|--|-----------|-----------------------------------|----------------------------|--------------------------------------|--|---|
| ISO 17366: supply chain applications of RFID – product packaging [separate UII memory, with Data Identifiers in separate memory] | 0xA5 | Not applicable | 6-bit | 25S | 1 0 15961 13 1 | 3 or 13 |
| | | | | 25T | 1 0 15961 13 3 | |
| | | | | I | 1 0 15961 13 96 | |
| ISO 17366: supply chain applications of RFID – product packaging, containing hazardous materials [separate UII memory, with Data Identifiers in separate memory] | 0xA6 | Not applicable | 6-bit | 25S | 1 0 15961 13 1 | 3 or 13 |
| | | | | 25T | 1 0 15961 13 3 | |
| | | | | I | 1 0 15961 13 96 | |
| ISO 17365: supply chain applications of RFID – transport unit, containing hazardous materials [separate UII memory, with Data Identifiers in separate memory] | 0xA7 | Not applicable | 6-bit | J | 1 0 15961 13 4 | 3 or 13 |
| | | | | 1J | 1 0 15961 13 36 | |
| | | | | 2J | 1 0 15961 13 156 | |
| | | | | 3J | 1 0 15961 13 157 | |
| | | | | 4J | 1 0 15961 13 159 | |
| | | | | 5J | 1 0 15961 13 37 | |
| | | | | 6J | 1 0 15961 13 38 | |
| ISO 17364: supply chain applications of RFID – returnable transport item, containing hazardous materials [separate UII memory, with Data Identifiers in separate memory] | 0xA8 | Not applicable | 6-bit | 1B | 1 0 15961 13 112 | 3 or 13 |
| | | | | 25B | 1 0 15961 13 2 | |
| Explicitly reserved for ISO 17363 | 0xA9 | | | | | |
| Explicitly reserved for ISO 17363 | 0xAA | | | | | |
| ISO/IEC 29174 for Mobile Item Identifier (MII) and additional data [separate UII memory, with Data Identifiers in separate memory] | 0xAB | 7 | Not applicable | Not applicable | 2 27 1 | 13 (As required by ISO/IEC 29175) |

| Organisation or Standard | AFI (HEX) | UII Encoded Data Format (Decimal) | Monomorphic-UII Compaction | Monomorphic-UII MH10 Data Identifier | Object Identifier for Unique Item Identifier (UII) | Data Format for additional data (Decimal) |
|--|-----------|-----------------------------------|-----------------------------------|--------------------------------------|--|---|
| 6C Toll Operators Coalition See Note C | 0xB0 | 30 encoded in DSFID = 0x3E | Application-defined 8-bit (octet) | Not applicable | 1 0 159161 15 | 30 encoded in DSFID = 0x3E |
| ISBT – for blood, tissue, organ and cellular therapy products | 0xBB | 30 encoded in DSFID = 0x3E | Not applicable | | Not applicable | 30 encoded in DSFID = 0x3E |
| IATA RP1740C baggage handling [separate UII memory] | 0xC1 | 12 | Not applicable | | 1 0 15961 12 1 | 12 |
| EDItEUR: library items (for 18000-3M1 tags, using ISO 28560 Part 2 and 3) | 0xC2 | 6 | Not applicable | | 1 0 15961 6 1 | 6 |
| EDItEUR: library items (for 18000-63 tags, with separate UII memory, using ISO TS 28560-4) | 0xC2 | Not applicable | URN Code 40 | | 1 0 15961 6 0 | 6 |
| GS1 EPCglobal (for 18000-63 tags, with separate UII memory) See Note D | N/A | Not applicable | Not applicable | | Not applicable | 9 See Note E |

Additional Notes:

- A. The registration for IATA for low volume assets, initially applies to IATA RP1640, with Relative-OID 5 assigned to the UII, and Relative-OIDs 6 and 7 reserved for possible alternative UIIs in future. Relative-OIDs 30 to 49 are used for encoding additional data in MB11. Some of these have values and functions assigned in RP1640, others are reserved under the control of IATA. As IATA defines other asset-related applications, they will require separate registration, using the same AFI and data format, but different Relative-OIDs.
- B. The registration for IPC is intended to cover a number of different applications over future years. The initial application addresses postal items and encodes what is known in the sector as an 'S10' code. The object Identifier for the UII for this application is 1 0 15961 14 A. The value 'X' in the table will have a different alphabetic or numeric character for each application. There will be no requirement to assign additional data constructs, just to update this note.
- C. The assignment to the 6C Toll Operators Coalition retains the AFI assigned to enable trials. The additional constructs are for an application-defined UII structure and for additional data bit-based data in MB11. The data encoding rules are defined by the Coalition. Standard ISO/IEC 15962 encoders can only pass through the bit encoding and shall not attempt to validate them, and decoders can only pass through the bit encoding to the application layer and not attempt to interpret them.
- D. The encoding of the UII shall be to rules defined in the GS1 Tag Data Standard, which uses a different method than the AFI.
- E. Data Format 9 refers specifically to GS1 Application Identifiers. In addition, any other registered Data Format may be used in Memory Bank 11.

Register of Packed Objects

| Data Format | Organisation | URLs | |
|-------------|--------------|----------------------|---|
| 9 | GS1 | Packed Objects table | http://www.gs1.org/gsm/kc/epcglobal/tds/15961-PO-Fmt9.csv |
| | | Data Dictionary | http://www.gs1.org/barcodes/technical/genspecs#where |

Register of Tag Data Profiles

None yet registered

Register of Mapping Tables

| Data Format | Organisation: function | URL |
|-------------|------------------------------|--|
| 13 | ANSI MH10.8 Data Identifiers | http://www.mhi.org/standards/di The mapping table is accessible from this link on the page: Assigned_Relative_OID_DI_table_10SEP2014.xls |